


## FARO MINI WALL

## FAROMINIW.B.12.927



IP67

IK07



### Product Information

Super compact LED luminaire for the enhancement of landscape and architectural details through refined accent lighting effects.

Installation	Wall, floor, ceiling mounting
Size / Weight	Ø 32 50x55x70 mm / 0.2 Kg
Colour	Black RAL9005 / Brass swivel
Body Material	A2 stainless steel with Brass swivel
Screen Material	Tempered glass
Fixing Position	Full orientation capability
Warranty	5 year warranty

### Technical Data

Light Source	LED
CCT (K) / CRI	2700K / 80 CRI (90 on request)
Luminous Efficacy	85lm/W
Delivered Lumen	255lm
Beam Angle	12° (narrow)
Power Consumption	3W
Current	900mA
Ingress Protection	IP67
Impact Resistance	IK07
Driver	Remote (to be ordered separately)
Operating temperature	-30°C to 40°C
Rated life	60,000hrs

### Accessories (to be ordered separately)

FAROMINIW.V.B - FARO MINI WALL VISOR BLACK RAL9005  
 FAROMINIW.V.W - FARO MINI WALL VISOR WHITE RAL9003

FAROMINIW.DRIVER.DALI - FARO MINI DRIVER DALI 30W IP20  
 FAROMINIW.DRIVER.ON-OFF - FARO MINI DRIVER ON-OFF