


FARO MINI WALL

FAROMINIW.W.12.930



Product Information

Super compact LED luminaire for the enhancement of landscape and architectural details through refined accent lighting effects.

Installation	Wall, floor, ceiling mounting
Size / Weight	Ø 32 50x55x70 mm / 0.2 Kg
Colour	White RAL9003 / Brass swivel
Body Material	A2 stainless steel with Brass swivel
Screen Material	Tempered glass
Fixing Position	Full orientation capability
Warranty	5 year warranty

Technical Data

Light Source	LED
CCT (K) / CRI	3000K / 80 CRI (90 on request)
Luminous Efficacy	91lm/W
Delivered Lumen	273lm
Beam Angle	12° (narrow)
Power Consumption	3W
Current	900mA
Ingress Protection	IP67
Impact Resistance	IK07
Driver	Remote (to be ordered separately)
Operating temperature	-30°C to 40°C
Rated life	60,000hrs

Accessories (to be ordered separately)

FAROMINIW.V.B - FARO MINI WALL VISOR BLACK RAL9005  
FAROMINIW.V.W - FARO MINI WALL VISOR WHITE RAL9003

FAROMINIW.DRIVER.DALI - FARO MINI DRIVER DALI 30W IP20  
FAROMINIW.DRIVER.ON-OFF - FARO MINI DRIVER ON-OFF